


The PBR panel profile is ideal for a variety of architectural, agricultural, commercial, and industrial applications. PBR panels are a multi-use roof and wall panel that are extremely durable and cost-effective. Waard offers a selection of coatings designed to protect metal panels including Signature® 200, Signature® 300, and Galvalume Plus®. The galvalume plus R panels are designed to resist damage from rust. PBR metal panels can be installed vertically or horizontally and are considered a staple.



CLOSE UP VIEW OF PBR PANELS

### PANEL MEASUREMENTS



### Product Specifications:

**Coverage Width:** 36"

**Length:** 5'-0" to 50'-0"

**Rib Height:** 1-1/4"

**Rib Spacing:** 12" on center

**Minimum Slope:** 1/2:12

**Material and Thickness:**

26 (standard); 24, 22 (optional) GA Galvalume

**Panel Attachment:** Exposed Fastening System

**Coatings:** Signature® 200, Signature® 300,  
Galvalume Plus®

### Application:

- Installed horizontally or vertically
- Ease of installation - can be applied directly to solid decking or open framing
- Typical applications include roofs, walls, ceilings, fascias, mansards, equipment screens, and soffits

### Performance Standards:

Ratings	UL 580, UL 790
External Fire	Class A
Internal Fire	Roof assembly for UL 263
Impact Rating	UL 2218, Class 4
Carries Florida Approval	
Dade county ratings and FM 4471 approval standard for class 1 panel roofs	